

F…ファイン（定尺4,000mmの在庫あり） H…HL（定尺4,000mmの在庫あり）
⑤…5,000mmの在庫あり ⑥…6,000mmの在庫あり

SUS304 化粧パイプ<ファイン・HL>							定尺4,000mm・単位：mm						
外 径	0.8	1.0	1.2	1.5	2.0	3.0							
5	F	F											
6	F	F											
7	F	F											
8	F	F H											
9	F	F											
10	F	F H											
12	F	F H											
13	F	F H	F H	F	H								
13.8				F	H								
14	F	※ F											
15	F	F											
16	F	F H	F H	F ⑤ ⑥ H ⑤ ⑥	F	H							
17.3				F	H	F	H						
19	F	F H	F H	F ⑤ ⑥ H ⑤ ⑥	F	H							
21.7		F	F H	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥	F ⑥	H						
22	F	F H	F H	F ⑤ ⑥ H ⑤ ⑥	F	H							
25	F	F H	F H	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥	F	H						
25.4			F	F	H	F	H						
27.2		F H	F H	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥						
32		F H	F H	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑥							
34		F	F H	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥							
38		F	F H	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥							
42.7			F H	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥							
45				F	H	F	H						
48.6			F H	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥							
50		F	F H	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥							
60.5				F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥							
76.3				F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥	F ⑤ ⑥ H ⑤ ⑥							
89.1				F	H	F ⑥	H ⑥						
101.6				F	H	F ⑥	H ⑥						
114.3						F ⑥	H ⑥						
139.8						F ⑥	H ⑥						
165.2												F ⑥	H ⑥
216.3												F ⑥	H ⑥

F H印は即納品です。「※」は受注生産になります。

豊富なサイズと豊富な在庫。
スチールは小ロットから
大量のご注文まで即納できます。

寸法の許容差

外 径 (mm)	許容差
50未満	±0.25mm
50以上76.3未満	±0.5%
76.3以上	±1.0%

厚 さ (mm)	許容差
3未満	±0.3mm
3以上	±10%

長 さ	許容差 (mm)
定尺品	+20 -0

真直度許容差	
長 さ (mm)	許容差 (mm)
1,000に対し	1.0以下

SUS304 配管パイプ

定尺4,000mm（一部6,000mmあり）・単位：mm													
呼び径		外径	1.5	2.0	2.5	3.0	3.5	4.0	5.0	5.2	5.5	6.0	6.5
A	B		kg/P	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P	kg/P
6	⅛	10.5	1.34	1.69									
8	¼	13.8	1.84	2.35		3.23							
10	⅜	17.3	2.36	3.05	3.69	4.28							
15	½	21.7	3.02	3.92	4.80	5.60							
20	¾	27.2	3.84	5.04	6.16	7.24							
25	1	34.0	4.84	6.36	7.84	9.28	10.6	12.0					
32	1 ¼	42.7	6.16	8.12		11.9	13.7	15.4					
40	1 ½	48.6	7.04	9.28		13.6	15.7	17.8					
50	2	60.5	8.8	11.6		17.2	19.9	22.5	27.6		30.2		
65	2 ½	76.3		14.8		21.9	25.4	28.8	35.5	36.8			
80	3	89.1		17.4		25.7		33.9	42.0		46.0		
90	3 ½	101.6		19.8		29.5		38.9					
100	4	114.3		22.4		33.3		44.0	54.4			64.8	
125	5	139.8		27.5		40.8	47.6	54.0	67.2				
150	6	165.2				48.4	56.4	64.4	80.0				
200	8	216.3				63.6		84.8	105.0				136.0
250	10	267.4				79.2	92.0	105.0	131.0				169.0
300	12	318.5				94.4		125.0					202.0
350	14	355.6						140.0	175.0			209.0	
400	16	406.4						161.0	201.0			240.0	
450	18	457.2						181.0	226.0			270.0	

※重量を表示しているサイズは即納品です。

寸法の許容差（配管用 JIS G 3459）				標準重量計算式		
外径許容差		長さ許容差		鋼 種	基本質量 (kg)	算 式 (W/m)
外 径 (mm)	許容差 (mm)	長 さ (mm)	許容差 (mm)	SUS304、304L	7.93	W=0.02491t (D-t)
30未満	±0.3	4,000未満	+10 0	SUS316、316L	7.98	W=0.02507t (D-t)
30以上	± (外径×1.0%)	4,000以上	+20 0			
厚さ許容差		真直度許容差				
厚 さ (mm)	許容差 (mm)	長 さ (mm)	許容差 (mm)			
2未満	±0.2	1,000に対し	1.0以下			
2以上	± (板厚×10%)					



SUS304 自動車用マフラーパイプ<ファイン研磨>			定尺4,000mm・単位：mm		
外 径	1.5				
50.8	F				

SUS430 化粧パイプ<ファイン研磨>					定尺4,000mm・単位：mm				
外 径	0.8	1.0	1.2	1.5					
13		F							
16		F	F	F					
19	F	F	F	F					
22		F	F	F					
25		F	F	F					
32		F	F	F					
38		F	F	F					

F 印は即納品です。

